

**Data-to-Data Installation (Included)**

**CAN Hi/Low Harness**

Wire	Color	Type	Location
CAN Hi	Brown	Data	PIN 6 OBD Connector
CAN Low	White	Data	PIN 14 OBD Connector



**Serial Cable**

Serial cable (4-pin) plugs into the gray port of the remote starter



**Hardwire T-Harness Installation (Sold Separately)**

**FT-HRN-X1-OBD**

Wire	Color	Type	Output Configuration
Ignition	Green	Input (+)	--
POC 1	Yellow	<ul style="list-style-type: none"> <li>• Aux 1</li> <li>• Aux 2</li> <li>• Lock/Arm</li> <li>• Unlock/Disarm</li> <li>• Starter Kill (can only be set as latched)</li> </ul>	<ul style="list-style-type: none"> <li>• Single Pulse</li> <li>• Double Pulse</li> <li>• Latched</li> </ul>
POC 2	Purple	<ul style="list-style-type: none"> <li>• Aux 1</li> <li>• Aux 2</li> <li>• Lock/Arm</li> <li>• Unlock/Disarm</li> <li>• Starter Kill (can only be set as latched)</li> </ul>	<ul style="list-style-type: none"> <li>• Single Pulse</li> <li>• Double Pulse</li> <li>• Latched</li> </ul>
POC 3	Blue	<ul style="list-style-type: none"> <li>• Aux 1</li> <li>• Aux 2</li> <li>• Lock/Arm</li> <li>• Unlock/Disarm</li> <li>• Starter Kill (can only be set as latched)</li> </ul>	<ul style="list-style-type: none"> <li>• Single Pulse</li> <li>• Double Pulse</li> <li>• Latched</li> </ul>
PIC 1	Pink	<ul style="list-style-type: none"> <li>• Pre-warn</li> <li>• Instant Trigger</li> </ul>	--



(optional)

**Caution:** Do not insert 3A fuse when connected to a remote start through data.